

GOTECH "the best partner" to raise your competition

GT-7001-HC 拉力試驗機專用高低溫箱 Temperature Chamber

本箱配合拉力機使用，適用於橡膠、皮革、彈性布、塑料、金屬等材料在高溫或低溫條件下作拉伸、張力、斷裂、剝離等試驗。

The GT-7001-HC is a specialized option designed for integration with Gotech's tensile strength tester. This temperature chamber is tailored to create a controlled temperature environment for conducting tensile, tearing, or peeling tests on a variety of materials, such as rubber, leather, elastic cloth, plastics, and metals.



了解更多產品信息，請登錄我司網站 www.gotech.biz

型號 Model	GT-7001-H	GT-7001-C3	GT-7001-C6
控溫方式 Temp. control	平衡調溫系統 · P.I.D.方式控制 Balancing system with P.I.D control		
溫度控制器 Operation system	按鍵式面板 Button panel	人機界面 Touchscreen	
溫度範圍 Temp. range	RT~250℃	-30℃~RT	-60℃~RT
控溫精度 Temp. accuracy	±1℃		
升溫速度 Heating speed	RT~250℃≤40min	-30℃~RT≤30min	-60℃~RT≤30min
降溫速度 Cooling speed	-	RT~-30℃≤50min	RT~-60℃≤60min
加熱方式 Heating mode	熱風循環 Hot wing cycle		
冷卻系統 Refrigeration system	-	全密閉式壓縮機單段式 Single stage, hermetic compressor	全密閉式壓縮機二段式 Hermetic compressor, cascade refrigeration system
冷媒 Refrigerant	-	環保冷媒 With environmental protection	
內箱及夾具 Inner chamber/grips	不鏽鋼 Stainless steel		
有效行程 (含RA-4-1夾具) Effective stroke (include RA-4-1 grips)	310mm (或接受訂製 or customization)		
標點伸長計 Elongation meter	選擇配置 U33LA as optional		
內箱體積 Interior dimension(W×D×H)	22 × 28 × 60 cm (或接受訂製 or customization)		
體積 Dimension(W×D×H)	55 × 225 × 170 cm		
電源 Power	1φ,AC220V,15A 50Hz/60Hz或指定or specify	1φ,AC220V,18A 50Hz/60Hz或指定or specify	1φ,AC220V,25A 50Hz/60Hz或指定or specify

型號 Model	GT-7001-HC3	GT-7001-HC6	GT-7001-HD8
控溫方式 Temp. control	平衡調溫系統 · P.I.D.方式控制 Balancing system with P.I.D control		
溫度控制器 Operation system	人機界面 Touchscreen		
溫度範圍 Temp. range	-30°C~150°C/-30°C~250°C(選購optional)	-60°C~150°C/-60°C~250°C(選購optional)	-80°C~250°C
控溫精度 Temp. accuracy	±1°C		
升溫速度 Heating speed	RT~150°C≤30min / RT~250°C≤35min	RT~150°C≤30min / RT~250°C≤35min	RT~250°C≤35min
降溫速度 Cooling speed	RT~-30°C≤50min	RT~-60°C≤60min	RT~-80°C≤20min
加熱方式 Heating mode	熱風循環 Hot wing cycle		
冷卻系統 Refrigeration system	全密閉式壓縮機單段式 Single stage, hermetic compressor	全密閉式壓縮機二段式 Hermetic compressor, cascade refrigeration system	液氮強制制冷 Liquid nitrogenrefrigeration system
冷媒 Refrigerant	環保冷媒 With environmental protection		
內箱及夾具 Inner chamber/grips	不鏽鋼 Stainless steel		
有效行程 (含RA-4-1夾具) Effective stroke (include RA-4-1 grips)	310mm (或接受訂製 or customization)		
標點伸長計 Elongation meter	選擇配置 U33LA as optional		
內箱體積 Interior dimension(W×D×H)	22 × 28 × 60 cm (或接受訂製 or customization)		
體積 Dimension(W×D×H)	55 × 225 × 170 cm		
電源 Power	1φ,AC220V,18A 50Hz/60Hz或指定or specify	1φ,AC220V,25A 50Hz/60Hz或指定or specify	1φ,AC220V,15A 50Hz/60Hz或指定or specify

■ 各式夾具及伸長量測裝置...等附件，依客戶需求（合約書）選配，本公司業務部也會給客戶最恰當之建議。

■ The accessories such as the different grips, elongation measuring-devices... etc. are equipped according to the requirements specified in the contract; our sales representative will also give the proper suggestions to our customer beforehand.



創於1977年——

高鐵科技股份有限公司

GOTECH TESTING MACHINES INC.

本廠: 台中市工業區24路28號

二廠: 台中市工業區24路31號

TEL: (04)23590061

FAX: (04)23591553

網址: www.gotech.biz E-mail: gt112@gotech.biz

高鐵檢測儀器(東莞)有限公司

GOTECH TESTING MACHINES CO., LTD.

地址: 廣東省東莞市南城區宏圖高新科技開發區宏三路

TEL: 0769-89986666

22400899

FAX: 0769-22400699

E-mail: gt-d130@gotech.biz

手機: 13926831580

高特威爾檢測儀器(青島)有限公司

GOODTECHWILL TESTING MACHINES CO., LTD.

地址: 中國青島市市北區哈爾濱路52號青建太陽島1號商務樓8層

TEL: 0532-85931956

85931957

FAX: 0532-85931950

E-mail: gt-q101@gotech.biz

手機: 13708970121